OraQuick ADVANCE Control Log

Were new controls opened today? Yes	
Were new controls opened today? Yes	l Control
Yes	☐ Yes
Were new controls opened today? Yes	□ No
No	☐ Yes ☐ No
opened today? Yes No New Operator New Shipment Test Area Temp Irregularity Outreach Location Were new controls opened today? New Operator New Shipment Routine New Lot Opened AM/PM	
Were new controls opened today? Yes No No No No Outreach Location Outreach Location AW/FM No Outreach Location	☐ Yes ☐ No
opened today? Yes New Operator New Shipment Test Area Temp Irregularity AM/PM AM/PM AM/PM AM/PM	
Outreach Location	☐ Yes ☐ No
Were new controls Described Describe	
opened today? Yes New Operator New Shipment Test Area Temp Irregularity AM/PM AM/PM AM/PM	☐ Yes ☐ No
Were new controls opened today? Yes No New Operator New Shipment Test Area Temp Irregularity AM/PM AM/PM AM/PM	☐ Yes ☐ No
Outreach Location Were new controls Routine New Lot Opened Yes	☐ Yes
opened today? ☐ Yes ☐ New Operator ☐ Storage Temp Irregularity ☐ New Shipment ☐ Test Area Temp Irregularity ☐ Outreach Location ☐ Outreach Location ☐ No	□ No
Were new controls opened today? Yes No New Shipment Test Area Temp Irregularity Outreach Location AM/PM AM/PM AM/PM	☐ Yes ☐ No

OraQuick ADVANCE Temperature Log

Month:	Year:

Control Storage Area		
Day	Temperature	
1	•	
2		
3		
1 2 3 4 5 6 7		
5		
6		
7		
8		
9		
10		
11		
12		
13		
14		
11 12 13 14 15 16 17		
16		
17		
18		
19		
20		
21 22 23 24		
22		
23		
24		
25		
26		
26 27		
28		
29		
30		
31		

OraQuick ADVANCE Controls must be stored at a			
temperature between	35°F and 46°F	. If the	
temperature for the co	ontrols storage	area falls outside	
this range, document corrective actions taken in the			
Corrective Action Log.			

5.	Storage Area	1.22.1.
Day	Temperature	Initials
1		
2		
3		
4		
1 2 3 4 5 6 7		
6		
7		
8 9		
9		
10		
11		
12		
13		
14		
12 13 14 15 16		
16		
17		
18		
19		
20		
21		
21 22		
23 24 25		
24		
25		
26		
27		
28		
29		
30		
31		

OraQuick ADVANCE test kits must be stored at a room temperature between 35°F and 80°F. If the temperature for the storage area falls outside this range, document corrective actions taken in the Corrective Action Log.

Day	Testing Area Temperature	Initials
1	Tomporataro	miliaio
2		
3		
4		
5		
6		
2 3 4 5 6 7		
8		
10		
11		
12		
13		
12 13 14 15		
15		
16 17		
17		
18		
19		
20		
21		
22		
21 22 23 24 25		
24		
25		
26		
27		
28		
29		
30		
31		

OraQuick ADVANCE test kits should be used at temperature ranges between 59°F and 99°F. If the temperature for the testing area falls outside this range, document corrective actions taken in the Corrective Action Log.